



From North America's #1 Brand  
of High-Pressure Cleaning Equipment

# HEAT Series

Indirect Portable Heaters

## RedHot Cannon Models Fuel Oil-Fired

### The Most Efficient Heaters in the Industry

Diesel indirect-fired portable heaters use an embedded burner with combustion air obtained from the main ventilation fan. The RedHot Cannon heaters feature a heat exchanger that contains the flame and expels fumes through a chimney connected to the outside. Being indirect-fired, they can be operated indoors and can also be ducted.

Combustion **air pressure switch** safety device automatically turns unit off if necessary

### Four Pass Heat Exchanger Technology

The new four pass heat exchanger technology allows exhaust gases to increase heat exchange with the cooling air and obtain maximum thermal efficiency.

Electric **control panel**



Automatic post-ventilation **cooling cycle** to cool down the combustion chamber

Hydrocarbon resistant **fuel lines**

HeatCannon 200

10" pneumatic **wheels**

Electronic **flame control** unit with metal casing

RedHot Cannon 200 and 300 models equipped with **pre-heat filter**

Controlled by the **thermostat, humidistat or timer**

## FEATURES

- Uses Kerosene, Diesel #1, Diesel #2 or Jet Fuel
- Approved for Construction
- CSA Approved
- Indirect-Fired, can be operated indoors and ducted

[www.Hotsy.com](http://www.Hotsy.com)

Nothing Heats Like a Hotsy!

# The Hotsy Heat Series: Indirect-Fired Heaters... With Four Pass Heat Exchanger Technology

## SPECIFICATIONS

	Measurement	RedHot Cannon 100	RedHot Cannon 200	RedHot Cannon 300
Heat Input	BTU/H	112,141	204,873	293,982
Heat Output	BTU/H	94,759	183,362	258,704
Fuel Consumption	GAL/H	0.81	1.48	2.17
Heated Airflow	CFM	1,020	1,530	2,530
Temperature Rise (@64°F)	°F	95	136	126
Power Supply	Volt, PH, HZ	120, 1, 60	120, 1, 60	120, 1, 60
Fan Motor Power	HP (RPM)	1/4 (3,300)	5/8 (3,300)	1 (1,700)
Current Rating	AMPS	4.05	7.65	11.80
Max Length Flex. Duct (One-Way)	FT	25	50	75
Max Length Flex. Duct (Two-Way)	FT	--	25	35
Flue Size	IN	6	6	6
Tank Capacity	GAL	11	17.2	27.7
Run Time	HOURLY	14	14	13
Dry Weight	LBS	143	238	330
Dimensions	IN	46L x 20W x 28H	52L x 20W x 38H	67L x 25W x 42H



### Providing Heat for Outdoor Settings

Since 1970, Hotsy has been a trusted name for high pressure cleaning equipment. Now we have introduced a line of infrared and forced-air heaters to make cleaning more comfortable.

Indirect heaters are ideal for heating outdoor event space, construction sites - even professional sports athletes in cold weather climates.

Hotsy's lineup of reliable radiant forced-air heaters and accessories delivers the heat you need to drive the results you demand. Better yet, they are backed by our network of authorized dealers throughout North America.



## OPTIONS

- Fuel Level Gauge
- Fuel Tank Filter
- 4 Lifting Brackets
- Single Fuel Line Kit
- 12" One-Way Duct Adapter (for 100 model)
- 14" One-Way Duct Adapter (for 200 model)
- 16" One-Way Duct Adapter (for 300 model)
- 12" Two-Way Duct Adapter (for 200 model)
- 12" Two-Way Duct Adapter (for 300 model)
- 20°F/120°F Heavy Duty Thermostat w/30' Cable and 90° Plug
- External Fuel Tank Connection Kit
- External Fuel Tank Connection Kit w/Deaerator (Tiger Loop)
- Pre-heated Oil Filter (for 100 model)
- 12" x 20' Flexible Air Duct
- 14" x 20' Flexible Air Duct
- 16" x 20' Flexible Air Duct

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631  
 www.Hotsy.com email: info@Hotsy.com  
 P/N 9.807-706.0 / HOT\_RED CAN Effective 10/17 Specifications & product  
 descriptions subject to change without notice.  
 A member of KÄRCHER North America



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models.